



McCoy Global products and services are subject to the Standard Terms and Conditions of Sale (or Rental) for McCoy Global Inc., both of which are available at mccoyglobal.com. For more information contact an authorized McCoy Global representative. Unless noted otherwise, trademarks and service marks herein are the property of McCoy Global, Inc. Specifications are subject to change without notice. McCoy Global, Inc. All rights reserved. v18

www.mccoyglobal.com | sales@mccoyglobal.com



MGT 10" 40K TONG HIGH PERFORMANCE POWER TONG



www.mccoyglobal.com | sales@mccoyglobal.com



MGT 10" 40K TONG

10" 40,000 FT/LBS HIGH PERFORMANCE POWER TONG


McCoy's all new MGT 10" 40K Tong was developed from ground-up to provide high torque and high speed (RPM) with the smallest possible operational footprint when making up connections of 4-1/2" to 10" size. Tong's main features are its compact design, light weight and small size that are critical for today's smaller rigs.



We conducted extensive testing on the MGT 10" 40K Tong to validate it is capable of consistent make-up and break-out of consecutive connections at 40,000 ft.lb. (its maximum torque rating). The tong offers full rotational capabilities at max torque rating. Its high torque for each pipe size meets industry's demand of increasing torque requirements.



As an option, we offer the most reliable in the industry Lockjaw Style Backup. With its three jaws technology, the Lockjaw Backup provides exceptional gripping capabilities with reduced pipe deformation, stress, and marking. The Backup offers a gripping range from 4-1/2" through 11-3/4" (114 mm to 298.5 mm).



BENEFITS

- High torque for each size from 9-7/8" to 4-1/2" to meet increasing torque requirements
- High RPM for improved running times
- Compact design for ease of use on small rigs
- Lighter weight for reduced handling risks
- Combined with a Lockjaw Back-up, the system provides a more precise control of connection makeup along with safety enhancements.
- Tong's gripping range 4-1/2" through 10" (114 mm to 254 mm)
- Backup (optional) gripping range 4-1/2" to 11-3/4" (114 mm to 298.5 mm)

SPECIFICATIONS

| | Low Speed | High Speed |
|----------------------------------|--------------------------------------|-------------------------------------|
| Max torque, K ft-lbs | 40 | 6 |
| Speed @ 60GPM | 7.7 RPM | 55.6 RPM |
| Torque arm length, in | | 34 |
| Mass w/o jaws, lbs | | 1,680 |
| Footprint width, in | | 32 |
| Length - door closed, in | | 54- ³ / ₄ |
| Length - door open, in | | 61- ⁵ / ₈ |
| Mass with Backup & w/o jaws, lbs | | 3,700 |
| Gripping range | Max: 10 | Min: 4- ¹ / ₂ |
| Backup gripping range | Max: 11- ³ / ₄ | Min: 4- ¹ / ₂ |