



TOUGH. TESTED. RELIABLE.



McCoy Global products and services are subject to the Standard Terms and Conditions of Sale (or Rental) for McCoy Global Inc., both of which are available at [mccoysglobal.com](http://mccoysglobal.com).  
For more information contact an authorized McCoy Global representative.  
Unless noted otherwise, trademarks and service marks herein are the property of McCoy Global, Inc. Specifications are subject to change without notice. McCoy Global, Inc. All rights reserved. v18

[www.mccoysglobal.com](http://www.mccoysglobal.com) | [sales@mccoysglobal.com](mailto:sales@mccoysglobal.com)



TOUGH. TESTED. RELIABLE.

## RLM01

### RELAY OUTPUT MODULE

### Relay Output Module

The RLM provides 4 configurable relay outputs for use with the LMC and SD50 base controllers. Because the RLM uses the mg-net network for communications the system can be scaled to meet most application requirements.

### Standard Configuration

- (4) N.O. / N.C. relay contacts
- Rated for 30VDC / 240 VAC at 10 amps
- Heartbeat monitoring for failsafe operations and error detection
- No device configuration required
- User assignable relays
  - Low power consumption
  - (4) Output relays

### Electric Specifications

Supply Voltage: 12 or 24 VDC (nominal)  
Supply Current: 200 mA (max)

### Environmental

Operational Altitude: < 1500 m  
Operating Temperature: -40 to 158°F (-40 to 70°C)  
Storage Temperature: -40 to 158°F (-40 to 85°C)



### Dimensions

Height: 3.30 in (8.38 cm)  
Width: 4.80 in (12.19 cm)  
Depth: 3.41 in (8.66 cm)  
Weight: <1 lbs (< 0.45 kg)