



MCCOY
GLOBAL
TOUGH. TESTED. RELIABLE.



McCoy Global products and services are subject to the Standard Terms and Conditions of Sale (or Rental) for McCoy Global Inc., both of which are available at mccoyglobal.com.

For more information contact an authorized McCoy Global representative.

Unless noted otherwise, trademarks and service marks herein are the property of McCoy Global, Inc. Specifications are subject to change without notice. McCoy Global, Inc. All rights reserved. v17.1.0

www.mccoyglobal.com | sales@mccoyglobal.com



TOUGH. TESTED. RELIABLE.

WE TORQ™ 100 WRENCH AND SPINNER



www.mccoyglobal.com | sales@mccoyglobal.com



weTORQ™ 100 WRENCH AND SPINNER

McCoy's weTORQ™ 100 an integrated wrench and spinner with enhanced torque and range of motion which reduces the need to have people on the rig floor. The weTORQ™ 100 is available with a positioner (as shown) or in a hanging version. Optional wireless/remote controls also available.



weTORQ™ 100 CONFIGURATION MODELS

STANDARD	OPTION
Complete Wrench and Spinner	Wrench Only
Positioner	Hanging
Onboard Manual	Wireless/Remote Control

weTORQ™ 100 SPECIFICATIONS

Spin/Wrench Tubular Range	3.5" - 9.5"	89mm - 241mm
Upper/Lower Clamp Tubular Range	4.0" - 9.5"	101mm - 241mm
Range of Torque Motion	75°	
Minimum Tool Joint Height	21"	533mm
Positioner Reach	Up to 144"	Up to 3,650mm
Make-up Torque	85,000 ft.-lb.	115,260 Nm
Break-out Torque	100,000 ft.-lb.	135,582 Nm
Hydraulic Pressure	2,900 psi	200 bar
Hydraulic Flowrate	34 GPM	132 L/min
Weight without Positioner	~4,500 lbs.	~2,045 kg
Weight with Positioner	~9,500 lbs.	~4,300 kg